



Supermicro 1U813

Supermicro 1U813 SETAC Solution

Product Description

Silicom SETAC introduces a unique new concept to the appliance industry: the use of a simple kit to allow branded, high- technology servers to be configured as hardware appliances.

By using Silicom SETAC with a standard server, you create an ideal network appliance that delivers the best of both worlds: server-grade reliability and front-end access, together with field-replaceable architecture and a stable state-of-the-art technology environment.



Key Features

- Complete family of appliance platforms from 1U to 3U
- Full integration of SETAC-technology
- Solution with the maximum port density on the market
- Supermicro chassis design and dimensions

Technical Specifications

General Technical Specifications	
1U	Specifications
Dimensions (WxHxD)	17.2" (437mm) X 1.7" (43mm) X 25.6" (650mm)
Type	1U Rackmount
Power Supply	520W cold-swap PS
Mainboard	mini-ITX, ATX, eATX (long version only)
Front Bays	4
Front Modules	up to 2 SETAC modules

Order Information

P/N	Description	Notes
SA1U1-X2B2-R	1U Server to Dual Express Module and Dual SAS HDD Appliances Converter (Entire Kit)	Included: 1 x SA1U1-B2S2-R 1 x SA1U3-A2B-R 2 x MCB#SACB-42
SA1U3-A2B-R	1U PCI Express Host Connector Interface Adapter	PCI Express x8 Host Connector