



Supermicro 3U835

Supermicro 3U835 SETAC Solution

Product Description

Silicom SETAC introduces a unique new concept to the appliance industry: the use of a simple kit to allow branded, high- technology servers to be configured as hardware appliances.

By using Silicom SETAC with a standard server, you create an ideal network appliance that delivers the best of both worlds: server-grade reliability and front-end access, together with field-replaceable architecture and a stable state-of-the-art technology environment.



Key Features

- Complete family of appliance platforms from 1U to 3U
- Full integration of SETAC-technology
- Solution with the maximum port density on the market
- Supermicro chassis design and dimensions

Technical Specifications

General Technical Specifications	
3U	Specifications
Dimensions (WxHxD)	17.7" (450mm) X 17.7" (450mm) X 25.6" (650mm)
Type	3U Rackmount
Power Supply	800W (1 + 1) Redundant w/ PFC
Mainboard	mini-ITX, ATX, eATX (long version only)
Front Bays	4
Front Modules	up to six

Expansion Slots	7x Full-height, Full-length Expansion slots
------------------------	---

Order Information

P/N	Description	Notes
SA3U1-AB-R	3U PCI Express Host Connector Interface Adapter	PCI Express x8 Host Connector
MCB#SACB-38	TWINAX PCI Express Mini-SAS Cable, 0.381meter	
MCB#SACB-60	TWINAX PCI Express Mini-SAS Cable, 0.61meter	